FLEXIBLE HOSE INJECTION SOLUTIONS							
PRODUCT	PART NUMBER		PRODUCT TYPE	SYSTEMS			
Flex Inject [®] Sealant Advanced	985		Leak Sealant in Hose	Up to 6 Tons			
Flash™ Detect Inject	990		UV Dye in Hose	Up to 6 Tons			
Super Change™ Inject	991	R22	Conversion Solution in Hose	Up to 6 Tons			
Boost Juice [®] Inject	992	System	Performance Additive in Hose	Up to 6 Tons			
Flex Inject® Sealant Total	995	Leal	Sealant with UV Dye in Hose	Up to 6 Tons			
985 (Blue)	990 (Green)	991 (Red)	yy2 (Orange)	yos (Yellow)			

VACUUM-SEALED CAN SOLUTIONS

PRODUCT	PART NUMBER	PRODUCT TYPE	SYSTEMS
Super Seal Sealant Advanced (Medium)	944KIT	Leak Sealant Kit (Hose Included)	1.5 - 5 Tons
Super Seal Sealant Advanced (Small)	947KIT	Leak Sealant Kit (Hose Included)	Up to 1.5 Tons
Super Seal Sealant Advanced (Large)	948KIT	Leak Sealant Kit (Hose Included)	5+ Tons
Super Seal Sealant Total (Small)	971KIT	Leak Sealant with UV Dye Kit (Hose Included)	Up to 1.5 Tons
Super Seal Sealant Total (Large)	972KIT	Leak Sealant with UV Dye Kit (Hose Included)	1.5 - 5 Tons
Flash™ Detect	980	UV Dye (20122 Hose Sold Separately)	Up to 5 Tons
Super Change [™]	981	R22 Conversion Solution (20122 Hose Sold Separately)	Up to 6 Tons
Boost Juice [®]	993KIT	System Performance Additive (Hose Included)	Up to 6 Tons



SYRINGE CARTRIDGE SOLUTIONS

993KIT

PRODUCT	PART NUMBER	PRODUCT TYPE	SYSTEMS
Sure Shot Sealant Advanced	983KIT	Leak Sealant Cartridge	Up to 6 Tons
Sure Shot Sealant Advanced 984		Leak Sealant Cartridge Replacement	Up to 6 Tons

LEAK DETECTION LIGHT SOLUTIONS

PRODUCT		PART NUMBER		PRODUCT TYPE
UV Pocket Light		89DC		UV Pocket Light
SEEKERmini™		84DCPLUS		UV LED Work Light
SEEKERmax™		87DCPLUS		UV LED Work Light
Patriot Rechargeable Light		111110		UV LED Pocket Light
Patriot Charger		111110A		Charger for Patriot Light
89DC	84DCPLUS	87DCPLUS	11110	111110A

What advantages does Super Change give contractors?

By using Super Change, contractors can eliminate:

- Flushing that saves up to 1 hour
- Oil removal that saves up to 3 hours
- Disconnecting linesets which saves up to 30 minutes
- Equipment replacement which saves up to 6 hours
- Gasket and O-ring replacement that saves up to 1 hour

Other opportunities to save time and reduce callbacks with Super Change include:

- Correcting oil logging in systems with long lineset runs and rises
- Replenishing the oil in the system with Super Change allows for renewed gaskets and O-rings

SUPER CHANGE SOLUTIONS



About DiversiTech

Founded in 1971, DiversiTech Corporation is the largest manufacturer of equipment pads. It is also the leading North American manufacturer and supplier of accessory components and related products for the heating, ventilation, air conditioning, and refrigeration (HVAC/R) markets. Headquartered in the metropolitan Atlanta, Georgia area, DiversiTech's mission to its customers is to simplify their work.

DiversiTech Corporation

6650 Sugarloaf Parkway Duluth, GA 30097 P 800.995.2222 F 678.542.3700 DOC146082 LIT-FLY-SC ©2018 DiversiTech Corp. www.diversitech.com

UPER CHA

ALL SYSTEMS I UP TO 20 KW TO 6 TONS 2021 60 ml VIDIM SALED



SUPER CHANGE[™] SOLUTIONS

SUPER CHANGE INJECT

SUPER CHANGE IN CAN (VACUUM-SEALED)

Super Change in a vacuum-sealed can has

the same benefits of Super Change Inject

INDUSTRY CHALLENGES WITH CONVERTING REFRIGERANTS

System Incompatibility

- Refrigerant and oil Super Change links the old with the new
- Oil logging Super Change eliminates this risk especially for systems with long lineset runs and rises
- Soft materials the chemical composition of Super Change directly reacts and absorbs into these soft components such as O-rings and gaskets (large systems) counteracting the contraction caused by the removal of the HCFC refrigerants

Unknown History with System

- Past Leakage How many times has the system been topped off? Has the oil been compromised after years of running? Super Change addresses these questions
- Moisture and Oxygen Super Change removes moisture and oxygen thus preventing corrosion and lubricant breakdown while restoring lubricant to its original condition



Watch a video on how Super Change works and learn more at www.diversitech.com/superchange

Super Change[™] in a can and Super Change[™] Inject allows professional HVAC/R contractors a fast and easy way to convert a system from non-POE based oils and refrigerants such as R22 to newer HFC refrigerants including POE-based R407C and R410A without the need to flush the system (excluding compressor burnouts). By adding Super Change with the new refrigerant and oil, a chemical link is created between the old and new oil, thus avoiding a full flush and saving contractors significant time on a system changeout.

Benefits include:

- No changeout of the oil, O-rings or gaskets required
- Replaces lineset flush
- Boosts oil return efficiency and extends compressor life
- Reduces oil logging which is critical in systems with long lineset runs and rises
- No tools or manifold gauges required
- Compatible with all oils and refrigerants
- No propellants making refrigerant reclaimable at later date if removed

Super Change is available in two different dispensing methods:

> **FAST & EASY** (HOSE AND CAN INJECTION SOLUTIONS)



Super Change Inject Part# 991

Super Change Part# 981

Super Change Inject uses DiversiTech's patent pending flexible hose and misting orifice technology to deliver fast and effective refrigerant changeouts. Super Change Inject uses the system's high side service port coupled with a push button device on the hose to inject the solution into the low side service port. With no runtime required after injection, the Super Change Inject formula goes to work immediately.

Application Guide

- One hose for systems up to 6 tons or 20 KW
- For more than 6 tons, use one additional hose for every 32 ounces of oil with large systems



Part# 991



SAVES TIME **ON SYSTEM** CONVERSIONS

NO TOOLS

BOOSTS

EFFICIENCY

REPLACES

LINESET

FLUSH



NO **CHANGEOUTS** REQUIRED

Super Change in can

Part# 981



Part# 20122 (Reusable hose sold separately)

and comes with a patented relief valve on the bottom. Super Change uses the system's refrigerant to install rather than REQUIRED a propellant such as butane or propane. With no runtime required after injection, the Super Change in can formula goes to work immediately.

Application Guide

ELIMINATES • One can for systems up to 6 tons or 20 MOISTURE KW

> For more than 6 tons, use one additional can for every 32 ounces of oil with large systems