

UT261 Series

Phase Sequence and Motor Rotation Indicators



UT261 series is used for determining 3-phase power phase sequence, missing phase indication, and motor phase rotation (UT261B). UT261A and UT261B can measure AC voltage of 40~700V and 90~600V respectively. These devices can operate in frequency range of 15~400Hz. UT261 are durable devices which can withstand impact from 2 meter's height. Test leads with protective tubing are included in optional accessories.

Specifications	UT261A	UT261B
Certificates	CE, UKCA, cETLus	
AC voltage (V)	90V~600V	40V~690V
Frequency (Hz)	15Hz~400Hz	15Hz~400Hz
Working current (A)	<1mA	<3mA
Phase sequence indication	LCD	LED
Missing phase indication	LCD	LED
Motor rotation indication		LED
Category rating	CAT III 600V	

Characteristics	
Standard accessories	Battery (UT261B), test lead with alligator clip x 3, English manual
Power	UT261A: No battery required; UT261B: 9V battery (6F22)
Product size	123 x 71 x 29mm
Product net weight	UT261A: 160g; UT261B: 180g
Standard individual packing	Gift box, carrying bag
Standard quantity per carton	20pcs
Standard carton measurement	450 x 325 x 340mm
Standard carton gross weight	UT261A: 9.8kg; UT261B: 10.3kg



UT261A



UT261B

